

CB MINERALS

875 Mamaroneck Ave. #305
Mamaroneck, NY 10543
Tel: 914-777-3330 Fax: 914-777-3035
WEBSITE: www.cbminerals.com
E-Mail: info@cbminerals.com
INDUSTRIAL MINERALS SINCE 1897

DOLOMITE 325 & 200 MESH

These are common Dolomitic Limestone powders used as fillers, for agriculture, acid neutralization, and a variety of other industrial processes where low cost is important

TYPICAL PROPERTIES

	<u>325 mesh</u>	<u>200 mesh</u>
Specific Gravity	2.8	2.8
Bulk Density (pounds/ft ³)	65	70
(grams/cc)	1.04	1.12
Dry Brightness (Hunter Y. Rd value)	89	88
Oil Absorption (grams/100 grams)	13	12

CHEMICAL SPECIFICATION:

Calcium Carbonate	CaCO ₃	55.0%
Magnesium Carbonate	MgCO ₃	43.0%
Iron as	Fe ₂ O ₃	0.3%
Moisture	H ₂ O	0.1%

PHYSICAL SPECIFICATION:

	<u>325 mesh</u>	<u>200 mesh</u>
Whiteness	89	88
Oil absorption	13	12
lb/cu ft	65	70
Spec. gravity	2.8	2.8
-75 micron	98%	91%
-20 micron	65%	55%
-10 micron	30%	25%
- 5 micron	20%	15%

PACKING: 50 lb. paper bags. 50 bags per pallet or Super Sacks

ORIGIN: USA